

BH520 SPECIFICATIONS



Bluetooth version: CSR8615-V4.0 CLASS2

Frequency range: 2.4GHz-2.480 GHz

Transmission distance: 10M (transmission distance due to environmental factors and mobile phone Bluetooth devices are different)

Working hours: 12 hours

Standby time: 250 hours

Support agreement: HFPV1.6, HSPV1.2, A2DPV1.2, AVRCPV1.4

Charging interface: Micro USB interface

Battery specifications: rechargeable lithium (3.7V, 180mAH)

Charging power: 5VDC, 100-240V AC adapter

Rated power: 3MW

Channel: Mono

Signal to noise ratio: $\geq 30\text{DB}$

Frequency response range: 20Hz-20KHz

Distortion: $\leq 1\%$

Speaker unit: OD 28mm

Microphone: single point anti-noise, impedance: $2.2\text{K}\Omega$; sensitivity: $40 \pm 3\text{dB}$

Use of the environment: Temperature: $0^\circ\text{C} \sim 40^\circ\text{C}$

Humidity: $0\% \sim 85\% \text{RH}$

Storage Environment: Temperature: $-30^\circ\text{C} \sim 40^\circ\text{C}$

Humidity: $0\% \text{ to } 90\% \text{RH}$